

BENCOR (Pty) Ltd.

Metering valves



Flow dividers type TQ and TV

The flow dividers type TQ divide (collect) total flow entering (exiting) port C. The distribution is independent of working pressure at ports A and B, and may be divided equally or unequally in predetermined portions.

The flow divider, type TV, features priority division. In other words, variable flow entering port C is divided where partial flow Q_A , through port A, is kept constant and the residual flow, Q_B , exits port B. As soon as one actuator's movement is stopped the flow to the other is either reduced to a minimal flow (type TQ) or completely reduced to leakage flow (type TV). It is possible to overcome this design feature by creating flow via pressure limiting flow.



These valves are used for applications where one pump is required to supply two unevenly loaded consumers which must be driven simultaneously and independently (type TQ) or if one actuator requires priority flow (type TV).

Nomenclature: Flow dividers with or without priority division

Design: Individual valve for pipe mounting or manifold mounting

Adjustability: Non-adjustable

P_{max} : 300 ... 350 bar

Q_{max} : 7,5 ... 200 l/min (nom. total flow)

Basic types and general parameters

Basic type and size	Flow Q_{max} (l/min)	Oper. pressure p_{max} (bar)	Tapped ports ¹⁾			Symbol	
			A	B	C	pipe mounting	manifold mounting
TV 3..	60	300	G 3/8	G 1/2	G 1/2		
TV 3P	60	300	---	---	---		
TQ 2..	7,5 ... 70	350	G 1/4, G 3/8	G 1/4, G 3/8	G 3/8		
TQ 3..	7,5 ... 70	350	G 3/8, G 1/2	G 3/8, G 1/2	G 1/2		
TQ 3P	7,5 ... 70	350	---	---	---		
TQ 4..	80 ... 120	350	G 1/2	G 1/2	G 3/4		
TQ 4P	80 ... 120	350	---	---	---		
TQ 5..	140 ... 200	350	G 3/4	G 3/4	G 1		
TQ 5P	140 ... 200	350	---	---	---		

¹⁾ for pipe mounting versions only

Additional versions

- Flow divider type TQ without reflow feature
- Flow divider type TQ with by-pass check valves enabling reflow

- Flow divider type TQ with unequal division

Order examples

TQ 32 - A3

Flow divider type TQ, size 3, tapped port size 2 (C = G 1/2; A, B = G 3/8), version A (dividing or collecting), with a nominal total flow $Q_{CN} = 45$ l/min (coding 3)

TV 3 - 2,5

Flow divider with priority division type TV, size 3, flow coding 2,5 ($Q_A = 5,8$ l/min)